

## IMAGE PICKUP LENS

**Patent number:** JP2001083409  
**Publication date:** 2001-03-30  
**Inventor:** SAITO TOMOHIRO; KANEKO ISAMU  
**Applicant:** ENPLAS CORP  
**Classification:**  
- **international:** G02B13/00  
- **europaean:**  
**Application number:** JP19990255581 19990909  
**Priority number(s):**

**Also published as:**




US6560043 (B1)

[Report a data error here](#)

### Abstract of JP2001083409

**PROBLEM TO BE SOLVED:** To provide an image pickup lens which is constituted so that desired optical performance can be maintained, a back focus distance can be sufficiently secured, a high telecentric property can be secured and respective aberrations can be excellently corrected and which can be easily manufactured.

**SOLUTION:** This image pickup lens is constituted by arraying a 1st positive-power lens 1 whose concave surface is formed at an object side near an optical axis, a 2nd negative-power lens 2 and a 3rd positive-power lens 3 in turn from the object side. At least the 1st surface of the lens 2 positioned at the object side out of the respective lenses 1, 2 and 3 is formed to be aspherical. Then, a diaphragm 4 is disposed between the lenses 1 and 2 and arranged at the more object side than a central point between the lenses 1 and 2. Besides, a light quantity regulating plate 5 is disposed at the 1st surface side of the lens 1. Then, a CCD being as the imaging device is mounted at the 2nd surface side of the lens 3 so that the image pickup surface 6 of the CCD is formed.



Data supplied from the **esp@cenet** database - Patent Abstracts of Japan